

# Fluxcored Cu-AL Rod



AWS ~

EN ISO ~

## APPROVALS:

## DESCRIPTION

Fluxcored Cu-AL Wire is our Aluminum Flux Cored Welding Rod for oxy-acetylene gas welding material such as 1060, 3003, 6061, 6063 etc.

## APPLICATIONS

- Refrigeration industry
- Air conditioning industry
- Condenser industry
- Power transformer
- Brazing of copper bar and aluminum foil

## MATERIALS TO BE WELDED

- 1060
- 3003
- 6061
- 6063

<b>SHIELDING GAS</b>	Oxy-acetylene
<b>POLARITY</b>	DC+
<b>AVAILABLE DIAMETERS</b>	1.6mm, 2.0mm
<b>PACKAGING</b>	Plastic Box - 2kg, Length: 500mm
<b>STORAGE</b>	Stored in a dry, enclosed environment, in its original undamaged packaging

## Flux ANALYSIS (WT%)

Flux ANALYSIS (WT%)					
Al	1,8 - 2,2	Cu	<0,30	Zn	remainder
Si	-	Mn	-	Ti	-
Fe	-	Mg	-	Be	-

## MECHANICAL PROPERTIES (WELDED METAL)

MECHANICAL PROPERTIES (WELDED METAL)			
0,2% Yield strength (MPa)	Tensile Strength (MPa)	Elongation L=5d (%)	Melting range °C
-	-	-	>500 °C

**Xinxiang Feeler Mechanical & Electrical Industry Co., Ltd.**